



- SPECIFICATIONS:**
- 240VAC +10%/-15% SINGLE PHASE 50/60HZ
  - 50°C MAXIMUM AMBIENT TEMPERATURE
  - NEMA 1 CORROSION RESISTANT
  - CE AND ETL COMPLIANT
  - 6.00in [150mm] CLEARANCE TO BE KEPT ON BOTTOM OF POWER SUPPLY FOR COOLING FANS  
REQUIRED FREE SPACE NEEDED FOR COIL REMOVAL
  - SEE THE FOLLOWING OUTLINE DRAWINGS FOR SEALING COILS:  
- UNIVERSAL COIL : G2107-5  
- TUNNEL COIL: G2107-6
  - OPTIONS: BASE PACKAGE

THIS PRINT IS THE PROPERTY OF PILLAR TECHNOLOGIES AND IS LOANED TO THE RECIPIENT SUBJECT TO RETURN UPON DEMAND. ITS CONTENTS ARE CONFIDENTIAL AND MUST NOT BE COPIED OR SUBMITTED TO OUTSIDE PARTIES FOR USE OR EXAMINATION

REV	DESCRIPTION	APP'D	DATE
REVISIONS			

<b>PILLAR TECHNOLOGIES</b> An ITW Company <small>475 INDUSTRIAL DRIVE HARTLAND, WI 53029 (262) 912-7200</small>		REF DWGS	
		FIRST USED ON	
DATE 11-12-15		DRAWN BY EJU	
TITLE		GENERAL OUTLINE	
		IFOILER	
		OPTIONS IN NOTES	
DWG NO		REV	
G2108-1		-	
SCALE 1:10		SHEET 1 OF 1	